



## MASTER LINE RUSTIC OAK

### Geometric characteristics (according to EN 13227)

|                        |                                 |
|------------------------|---------------------------------|
| Thickness              | 9mm                             |
| Width                  | 180/220/240/260 mm              |
| Length                 | 1000 to 2500mm                  |
| Tolerance in thickness | +/- 0,2mm                       |
| Tolerance in width     | +/- 0,2mm                       |
| Moisture content       | Between 7% and 11%              |
| Weight                 | +/- 7kg/sqm                     |
| Packaging              | per 10 pcs, the 260mm per 6 pcs |
| Bevel                  | With or without bevel/ u-bevel  |

### Specification wood species

|                                  |  |
|----------------------------------|--|
| Wood species                     | European oak   |
| Botanical name                   | quercus robur  |
| Area of growth                   | France   |
| Classification                   | Rustic / Rustick A, symbol □□, according to "Classifications for solid oak lamparquet used in the Benelux". A more strict classification than the EN 13227 |
| Sound sapwood                    | Not permitted  |
| Sound and intergrown knots (1)   | Ø ≤ 30mm   |
| Unsound knots (1)                | Ø ≤ 10mm   |
| Surface checks                   | Permitted  |
| Bark pocket                      | Not permitted  |
| Lightning shake                  | Not permitted  |
| Colour variation                 | Natural discoloration and indistinct defects caused by drying or stick marks permitted   |
| Slope of grain and medullary ray | Permitted  |
| Bio deterioration                | Not permitted  |
| Saw cut                          | Free   |

(1) Measurement method for knots according to EN 1310